

PRODUCT SPECIFICATIONS

FlashLink® USB Logger In-Transit Data Logger



- Large, easy to read LCD display
- Trip history statistics available on LCD
- Single-use
- USB Connection
- NIST traceable and CE Mark
- IP56 water-resistant rating
- Print data using Graphics Printer, FlashPDF software or download to PC
- Patented Shadow Log feature guarantees data even if the operator fails to start the unit

Recording Period	Internal Sensor		Logging Intervals
	°F	°C	
5-day	20910	20914	1 min 54 sec
15-day	20911	20915	5 min 40 sec
45-day	20912	20916	16 min 58 sec
75-day	20913	20917	28 min 16 sec

DeltaTRAK's FlashLink USB Logger is the ideal device for documenting storage and transport conditions of temperature-sensitive products.

Measurement Range	-40°F to 149°F (-40°C to 65°C)
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F from 14°F to 77°F (±.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	2 seconds typical for 3823 points
Factory Programmable Alarm Levels	High & Low levels over entire range, displayed on LCD
Battery	(CR2032) 3.6V Lithium/18 months
Dimensions/Body	1.575" x 3.189" x .575" (40mm x 81mm x 15mm)
Casing	PC/ABS plastic
Weight	1.3 oz. (36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, ROHS Compliant
Display	LCD, Red LED Alarm
Waterproof Rating	IP54
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
Min. System Requirements	Windows PC with XP or Windows 7 operating system
Download Requirements	Direct USB connection to PC. View data with free software downloaded from our web site.

DeltaTRAK manufactures products under an ISO 9000 registered quality management system

11D1