

# MiniRAE Lite

## Portable Handheld VOC Monitor



**Accurate VOC monitoring**

**Fastest response time (3 sec)**

**Humidity compensation**

**Easy to maintain and operate**

**Three-year lamp warranty**

The MiniRAE Lite is the most reliable handheld volatile organic compound (VOC) monitor on the market. Its photoionization detector's (PID) range of 0 to 5,000 ppm makes it an ideal instrument for applications ranging from environmental to construction.

### Key Features

- Proven PID technology—The patented sensor provides the following unique features:
  - 3-second response time
  - range up to 5,000 ppm
  - humidity compensation
- Designed for service—Easy access to lamp and sensor in seconds without tools
- Big graphic display for easy overview of concentration
- Field-interchangeable battery pack, replaceable in seconds without tools
- Integrated flashlight for better visibility in low light
- Multi-language support with 12 languages encoded
- Rugged housing withstands use in harsh environments
  - IP-65 design
  - Strong, protective removable rubber boot




### Additional Advantages

- Duty-cycling™ lamp and sensor auto-cleaning technology
- Tough, flexible inlet Flexi-Probe™
- Large keys are operable with 3 layers of gloves
- Strong, built-in sample pump draws up to 100' (30m) horizontally or vertically
- Loud, 95 dB audible alarm
- Bright red flashing visible alarm
- Interchangeable drop-in Lithium-ion and alkaline battery packs
- 3-year 10.6 eV lamp warranty



*MiniRAE Lite shown in optional Cradle*



# MiniRAE Lite

## Specifications

### Sensor Specifications\*

Gas Monitor	Range (ppm)	Resolution (ppm)	Response Time (T90)
VOCs	0 to 999.9	0.1	< 3 sec
VOCs	1000 to 5,000	1	< 3 sec

### Monitor Specifications\*

<b>Size</b>	10" L x 3.0" W x 2.5" H (25.5 x 7.6 x 6.4 cm)
<b>Weight</b>	26 oz (738 g)
<b>Sensors</b>	Photoionization sensor with standard 10.6eV lamp
<b>Battery</b>	• Alkaline battery adapter • External field-replaceable lithium-ion battery pack, if specified
<b>Operating Hours</b>	12 hours of operation on alkaline battery adapter (12 hours with lithium-ion battery pack)
<b>Display Graphic</b>	4 lines, 28 x 43 mm, with LED back light
<b>Keypad</b>	1 operation and 2 programming keys, 1 flashlight on/off
<b>Direct Readout</b>	Instantaneous reading of: • VOCs as ppm by volume • High and low values • Date and time
<b>Alarms</b>	95 dB buzzer (at 30 cm) and flashing red LED to indicate exceeded preset limits • High: 3 beeps and flashes per second • Low: 2 beeps and flashes per second • Alarm latching with manual override or automatic reset • Additional diagnostic alarm and display message for low battery and pump stall
<b>EMI/RFI</b>	Highly resistant to EMI/RFI. Compliant with EMC directive 89/336/EEC
<b>IP Rating</b>	IP-65
<b>Calibration</b>	Two-point calibration for zero and span
<b>Sampling Pump</b>	• Internal, integrated flow rate at 400 cc/min • Sample from 100' (30m) horizontally and vertically
<b>Low Flow Alarm</b>	Auto shut-off pump at low-flow condition
<b>Hazard Area Approval</b>	None
<b>Operating Temperature</b>	-4° to 113° F (-20° to 50° C)
<b>Humidity</b>	0 to 95% relative humidity (non-condensing)
<b>Attachments</b>	Durable green rubber boot
<b>Warranty</b>	3 years for 10.6 eV lamp, 1 year for pump, battery and instrument

\*Specifications are subject to change

## MiniRAE Lite Ordering Options

### Monitor only includes:

- MiniRAE Lite Monitor, Model PGM-7300
- RAE Systems 10.6 eV UV lamp
- Flex-I-Probe
- External filter
- Green rubber boot
- Alkaline battery adapter
- Lamp cleaning kit
- Tool kit
- Lithium-ion (Li-ion) battery, if specified with universal AC/DC charger and international plug kit
- Travel charger, if specified
- Universal wall adapter, if specified
- Operation & Maintenance manual
- Soft leather carrying case

### Monitor with accessories kit adds:

- Hard transport case with pre-cut foam
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

### Optional calibration kit adds:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

## Ordering Information

### Part Numbers

#### Monitor only with alkaline battery adapter

P/N 059-A100-000

#### Monitor with rechargeable Li-ion battery, accessory and calibration kit

P/N 059-A110-100

**Toll-Free: 877-723-2878**

[www.raesystems.com](http://www.raesystems.com)

**RAE Systems Inc.**  
3775 North First Street  
San Jose, CA 95134 USA  
raesales@raesystems.com

USA/Canada 1-877-723-2878  
Europe/Russia +45 8652 5155  
Middle East/Australia +971 4 3639 427  
China +86 10 58858788  
Asia +852 2669 0828

