

Digital Display Environmental Temperature Recorder



Models 18020 to 18031



This next-generation family of reusable environmental temperature recorders offer analog temperature recording along with an accurate digital temperature display feature for instant, easy viewing and permanent record-keeping.

- Highly visible LCD display and large window for viewing current and recently chart recorded temperature data
- Light weight, compact and battery operated, can be wall-mounted, or hung from a loop
- Wall-mounting bracket, screws and QC chart provided
- 12 models in °F and °C scales and two temperature ranges for **3-Day, 10-Day, 31-Day** and **62-Day** time intervals

Low Temp Range	-20°F to 100°F (-28°C to 38°C)
High Temp Range	30°F to 150°F (0°C to 65°C) High Temp Range
Accuracy	Chart and Scale: ±1.8°F (±1.0°C) LCD: ±1.8°F (-20°C to 165°C), ±1.0°C (-7°C to 74°C)
LCD Display/Chart Window	1.5" x 0.5" (3.8cm x 1.3cm)/2" x 2.8" (5cm x 7.1cm)
Sensor	Bi-metal coil/thermistor
Chart	Pressure-sensitive 36-inch strip
Drive	Solid-state quartz motor
Certification	CE mark, RoHS compliant
Battery	AAA alkaline (3-year shelf life; 1 to 2 years operating life)
Weight	1.1 lb (500 grams)
Dimensions	4in. x 7in. x 2.25in. (10.2cm x 17.8cm x 5.72cm)
Casing material	High impact ABS

7/15/08 Rev.1.0



DeltaTRAK

1-800-962-6776

P.O. Box 398 Pleasanton CA 94566

www.deltatrak.com

(925) 249-2250 Fax (925) 249-2251