

PRODUCT SPECIFICATIONS

FlashLink® USB Logger Reusable Data Logger



Model 20901

- User Programmable: manual or automatic start, sample interval, alarm limits, data tags
- Large, easy to read LCD display
- Trip history statistics available on LCD
- Patented Shadow Log feature guarantees data even if the operator fails to start the unit in manual mode
- Download to PC with FlashPDF Program Manager Software PN 20412
- NIST traceable and CE Mark
- Internal sensor shows ambient air temperature
- USB Connection
- Reusable

DeltaTRAK's FlashLink USB Logger is the ideal device for documenting temperature conditions during storage and transport of temperature-sensitive products.

Measurement Range	-40°F to 149°F (-40°C to 65°C)
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F from 14°F to 77°F (±.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	2 seconds typical for 3823 points
Programmable Alarm Levels	High & Low levels over entire range, displayed on LCD
Battery	(CR2032) 3.6V Lithium/18 months
Dimensions/Body	1.575" x 3.189" x .575" (40mm x 81mm x 15mm)
Casing	PC/ABS plastic
Weight	1.3 oz. (36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, ROHS Compliant
Display	LCD, Red LED Alarm
Waterproof Rating	IP54
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
Min. System Requirements	Windows PC with XP or Windows 7 operating system
Download Requirements	Direct USB connection to PC. Program logger and view data with FlashPDF Program Manager software. PN# 20412

DeltaTRAK manufactures products under an ISO 9000 registered quality management system

11D2